

PRODUCT DATA SHEET

2 IN 1 SM6236E Contact and Non-contact Tachometer

2 IN 1 tachometer is equipped with a large LCD display for clear readings. The contact accessories and photoelectric accessories can be interchanged at any time, realizing multiple functions in one machine. And it will automatically prompt when the power supply voltage is lower than the specified value



- Digits 18mm (0.6") White backlight LCD
- Accuracy: $\pm(0.05\%+1 \text{ digit})$
- Sampling Time: 0.5 sec(over 120RPM)
- Range Select: Auto-Ranging
- Memory: Max. value, Min. value, Last value. 96 data storage.
- Time Base: 6MHz Quartz crystal
- Detecting Distance: 50 to 500mm

Specification

Measuring Range:

- Photo Tach: 2.5 to 99,999RPM
- Contact Tach: 0.5 to 19,999RPM
- Surface Speed: 0.05 to 1,999.9m/min

Resolution

- Photo Tach: 0.1RPM (2.5 to 999.9RPM)
- 1RPM (over 1,000RPM)
- Contact Tach: 0.1RPM (0.5 to 999.9RPM)
- Surface Speed: 0.01m/min(0.05 to 99.99m/min)
- 0.1m/min(over 100m/min)
- Battery: 3x1.5V AAA



ติดต่อบริษัท เนโอนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th