

PRODUCT DATA SHEET

PM6208A Contact Tachometer



Features

1. Applying the MCU and electrooptical technology, can perform contact measurement of rotating & linear rolling speed efficiently.
2. Wide measuring range and high resolution
3. Large LCD display
4. Automatically store the Max, Min and LAST value
5. Accessories convertible for different measurement
6. Equipped with convex channel lineal rate sensor, it is convenient for measuring the lineal rate of the wire, cable, ropes etc.
7. Low battery indication
8. ELEGANT and easy to use.
9. Solid structure built with durable electronic elements and light ABS plastic house.

Specification

- Contact Measurement 50~19999RPM $\pm(0.03\%+2)$
- Auto Power Off 30S
- MAX/MIN/AVG Functions
- m/min m/sec ft/min ft/Sec in/min unit selection
- Data Logging 100 groups
- Data Hold
- Display Back light
- Low Battery indication
- Power Supply : 4×1.5AAA Battery
- Product Size : 193mm x60mm x 29mm
- Product Weight : 120g
- Packing Weight : 300g
- Packing Size : 189*111*62mm



ติดต่อบริษัท นีโอนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th