

Specifications	Range	Accuracy	
		HT112A	HT112B
DC Voltage	60mV/600mV/6V/60V/600V		±(0.5%+3)
	2V/20V/200V/600V	±(0.5%+3)	
AC Voltage	60mV/600mV/6V/60V/600V		±(1.0%+3)
	2V/20V/200V/600V	±(1.0%+3)	
DC Current	6000uA/60mA/600mA		±(1.2%+5)
	20mA/200mA/600mA	±(1.2%+5)	
AC Current	6000uA/60mA/600mA		±(1.5%+5)
	20mA/200mA/600mA	±(1.5%+5)	
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ		±(1.0%+5)
	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(1.0%+5)	
Capacitance	6nF/60nF/600nF/6μF/60μF/600μF/6mF/60mF		±(4.0%+5)
Frequency	10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz		±(1.0%+5)
Duty	1%~99%		±(3.0%+5)
Counts		2000	6000
Auto/Manual Range		Auto	Auto
Smart Function		✓	✓
Auto Recognition Of Probe Inserted Into Current Input		✓	✓
Tips Of Blow The Fuse		✓	✓
Live Test		✓	✓
NCV		✓	✓
Diode Test		✓	✓
Continuity		✓	✓
Data Hold		✓	✓
True RMS		✓	✓
Low Battery Indication		✓	✓
Auto Power Off		✓	✓
Backlight		✓	✓
Flashlight		✓	✓
Power	2 x 3V CR2032 batteries		
Weight	Approx. 128g		
Size	133X68X19mm		
QTY	50pcs		
Safety Rating	EN61010-1,-2-030; EN61010-2-033, EN61326-1, CAT III 600V		



ติดต่อบริษัท เนโอนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939 E-mail: sale@tools.in.th หรือ sale@neonics.co.th

