

Specifications	Range	Accuracy	
		HT113B	HT113C
DC Voltage	400mV/4V/40V/400V/600V	±(0.5%+3)	
	600mV/6V/60V/600V		±(0.5%+3)
AC Voltage	400mV/4V/40V/400V/600V	±(1.0%+3)	
	600mV/6V/60V/600V		±(1.0%+3)
DC Current	400uA/4000uA/40mA/400mA	±(1.2%+3)	
	600uA/6000uA/60mA/600mA		±(1.2%+3)
	10A	±(2.0%+3)	±(2.0%+3)
AC Current	400uA/4000uA/40mA/400mA	±(1.5%+3)	
	600uA/6000uA/60mA/600mA		±(1.5%+3)
	10A	±(2.0%+3)	±(2.0%+3)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1.0%+3)	
	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ		±(1.0%+3)
Capacitance	10nF/100nF/1μF/10μF/100μF/1mF/10mF		±(4.0%+5)
	100mF		±(5.0%+5)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz		±(1.0%+3)
Duty	1%~99%		±(3.0%+3)
Display		4000 Counts	6000 Counts
Auto/Manual Range		Auto	Auto
Live Test			✓
NCV		✓ (LED and buzz)	✓ (LED and buzz)
Diode Test		✓	✓
Continuity		✓ (LED and buzz)	✓ (LED and buzz)
Max Data Hold		✓	✓
Data Hold		✓	✓
True RMS		✓	✓
Bandwidth		40~1KHz	40~1KHz
Battery Test (1.5V/9V)		✓	
Low Battery Indication		✓	✓
Auto Power Off		✓	✓
Back Light		✓	✓
Work Light		✓	✓
Power		2x1.5V AAA batteries	
Weight		Approx.206g	Approx.206g
Size	151X75X48mm		
QTY	50pcs		
Safety Rating	EN61010-1,-2-030; EN61010-2-033, EN61326-1, CAT III 600V		



ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th