



6000 Counts Digital Multimeter with T-RMS/Autorange

HT118A

Specifications	Range	Accuracy
DC Voltage	600mV/6V/60V/600V/1000V	±(0.5%+3)
AC Voltage	600mV	±(0.8%+5)
	6V/60V/600V/750V	±(0.8%+5)
DC Current	600uA/6000uA/60mA/600mA	±(0.8%+3)
	10A	±(1.2%+3)
AC Current	600uA/6000uA/60mA/600mA	±(1.0%+3)
	10A	±(1.5%+3)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+3)
Capacitance	10nF/100nF/1μF/10μF/100μF/1mF/10mF	±(4.0%+3)
	100mF	±(5.0%+5)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	±(1.0%+3)
Duty	1%~99%	±(1.0%+2)
Temperature (°C/°F)	-40°C~1000°C	±(1.0%+3)
	-40°F~1832°F	±(1.0%+3)
Counts		6000 Counts
Auto/Manual Range		Auto
Display		LCD dual display
Bargraph		✓
Live Test (Sound And Light Alarm)		✓
NCV (Sound And Light Alarm)		✓
Diode Test		✓
Continuity (Sound And Light Alarm)		✓
Max/Min Hold		✓
Data Hold		✓
True RMS		✓
Bandwidth		1kHz
Low Battery Indication		✓
Auto Power Off		✓
Double Color Backlight		✓
Input Jack Led Indicate		✓
Work Light		✓
Power	2x1.5V AA batteries	
Weight	Approx.325g	
Size	188x88x58mm	
QTY	40pcs	
Safety Rating	EN61010-1,-2-030; EN61010-2-033, EN61326-1, CAT III 1000V, CATIV 600V	

