

HT118C/D

6000 Counts Digital Multimeter with T-RMS



Specifications	Range	Accuracy	
		HT118C	HT118D
DC Voltage	600mV/6V/60V/600V/1000V	±(0.5%+3)	±(0.5%+3)
AC Voltage	6V/60V/600V/750V	±(0.8%+5)	±(0.8%+5)
DC Current	60uA/60mA/600mA	±(0.8%+3)	±(0.8%+3)
	10A	±(1.2%+3)	±(1.2%+3)
AC Current	60mA/600mA	±(1.0%+3)	±(1.0%+3)
	10A	±(1.5%+3)	±(1.5%+3)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+3)	±(0.8%+3)
Capacitance	10nF/100nF/1μF/10μF/100μF/1mF/10mF	±(4.0%+3)	±(4.0%+3)
	100mF	±(5.0%+5)	±(5.0%+5)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	±(1.0%+3)	±(1.0%+3)
Duty	1%~99%	±(1.0%+2)	±(1.0%+2)
Temperature (°C/°F)	-40°C~1000°C	±(1.0%+3)	
	-40°F~1832°F	±(1.0%+3)	
Counts		6000	6000
Auto/Manual Range		Manual	Manual
Display		LCD dual display	LCD dual display
Live Test (Sound And Light Alarm)		✓	✓
NCV (Sound And Light Alarm)		✓	✓
Diode Test		✓	✓
Continuity (Sound And Light Alarm)		✓	✓
Max/Min Hold		✓	✓
Data Hold		✓	✓
True RMS		✓	✓
Bandwidth		1kHz	1kHz
Battery Test (1.5V/9V)		✓	✓
Low Battery Indication		✓	✓
Auto Power Off		✓	✓
Double Color Backlight		✓	✓
Input Jack Led Indicate		✓	✓
Work Light		✓	✓
Power	2x1.5V AA batteries		
Weight	Approx.325g		
Size	188x88x58mm		
QTY	40pcs		
Safety Rating	EN61010-1,-2-030; EN61010-2-033, EN61326-1, CAT III 1000V, CATIV 600V		



ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939 E-mail: sale@tools.in.th หรือ sale@neonics.co.th