

Specifications	Range	Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.08%+5)
AC Voltage	200mV/2V/20V/200V/750V	±(1.0%+25)
DC Current	200uA/2000uA/20mA/200mA	±(0.5%+5)
	10A	±(1.0%+15)
AC Current	200uA/2000uA/20mA/200mA	±(1.0%+25)
	10A	±(1.5%+25)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ	±(1.0%+15)
	20MΩ/100MΩ	±(3.0%+25)
Resistance	20nF/200nF/2μF/20μF/200μF/2mF	±(4.0%+50)
Resistance	200Hz/2kHz/20kHz/200kHz/2MHz/10MHz	±(1.0%+10)
Duty	1%~99%	±(3.0%+30)
Temperature	-20°C~1000°C	±(1.0%+2°C)
	-4°F~1832°F	±(1.0%+2°F)
Counts		20000
Display		LCD dual display
Bargraph		✓
Live test		✓
NCV		✓
Diode Test		✓
Continuity		✓
Max/Min Hold		✓
Data Hold		✓
True RMS		✓
Low Battery Indication		✓
Auto Power Off		✓
Double Color Backlight		✓
Input Jack Led Indicate		✓
Work Light		✓
Power	2x1.5V AA batteries	
Weight	Approx.325g	
Size	188x88x58mm	
QTY	40pcs	
Safety Rating	EN61010-1,-2-030;EN61010-2-033,EN61326-1,CAT III 1000V, CATIV 600V	

