

HT127A/B

6000 Counts Smart Digital Multimeter

NEW



Specifications	Range	Accuracy	
		HT127A	HT127B
DC Voltage	600mV/6V/60V/600V	±(0.5% +3)	±(0.5% +3)
AC Voltage	6V/60V/600V	±(0.8% +3)	±(0.8% +3)
DC Current	600mA/10A	±(1.2%+3)	±(1.2%+3)
AC Current	600mA/10A	±(1.5%+3)	±(1.5%+3)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(1.0%+3)	±(1.0%+3)
Capacitance	6nF/60nF/600nF/6μF/60μF/600μF/6mF	±(3.0%+5)	±(3.0%+5)
Frequency	60Hz/600Hz/6kHz/60kHz/600kHz/6MHz/10MHz	±(1.0%+3)	±(1.0%+3)
Duty	1.0~99.0%	±(3.0%+3)	±(3.0%+3)
Temperature (K-Type)	-40°C~1000°C(-40°F~1832°F)	±(1.0%+3)	±(1.0%+3)
Diode	0~3V	✓	✓
NCV	Audio and light alarm	✓	✓
Live	Audio and light alarm	✓	✓
Continuity	<50Ω	✓	✓
Counts		6000	6000
Display		TN	VA
Analog Bar		✓	✓
Gear Display		✓	✓
True RMS		✓	✓
Data Hold		✓	✓
Auto/Manual Range		Auto	Auto
Backlight		✓	✓
Flashlight		✓	✓
The Probe Insert Error Tips		✓	✓
Input Jack Indication		✓	✓
Fuse Burnt Indication		✓	✓
Low Battery Indication		✓	✓
Auto Power Off		✓	✓
Power	4x1.5V AAA batteries		
Weight	Approx.187g		
Size	145X72X26mm		
QTY	50pcs		
Safety Rating	EN61010-1,-2-030; EN61010-2-033, EN61326-1, CAT III 600V		



ติดต่อบริษัท เนโอนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939 E-mail: sale@tools.in.th หรือ sale@neonics.co.th