

| Function | WT816 | WT816A |
|---|-------|--------|
| Air Velocity & Temperature Measurement | √ | √ |
| Max/Average/Current air velocity measurement | √ | √ |
| °C/°F Temperature unit selection | √ | √ |
| Fives units of air velocity (M/s, Km/h, ft/min, Knots, mph) | √ | √ |
| Beaufort scale | √ | √ |
| Backlight display | √ | √ |
| Manual/Auto power shut off | √ | √ |
| Wind chill indication | √ | √ |
| Low battery indication | √ | √ |
| Waterproof IP67 | x | √ |

| Specification | | | | |
|-----------------------|-------------------------|-------------|--------------------|----------|
| Air velocity | | | | |
| Unit | Range | Resolution | Minimum wind speed | Accuracy |
| m/s | 0~30 | 0.1 | 0.7 | ±5% |
| ft/min | 0~5860 | 19 | 137 | |
| knots | 0~55 | 0.2 | 1.4 | |
| km/h | 0~90 | 0.3 | 2.5 | |
| mph | 0~65 | 0.2 | 1.6 | |
| Temperature | | | | |
| Unit | Range | Resolution | Accuracy | |
| °C | -10°C~45°C | 0.2 | ±2°C | |
| °F | 14°F~113°F | 0.36 | ±3.6°F | |
| Operating temperature | -10°C~45°C(14°F~113°F) | | | |
| Operating humidity | Less than 90%RH | | | |
| Store temperature | -40°C~60°C(-40°F~140°F) | | | |
| Battery | CR2032 3.0V (Included) | | | |
| Thermometer | NTC thermometer | | | |
| | WT816 | WT816A | | |
| Dimension | 40x18x105mm | 47x21x126mm | | |
| Weight | 52g | 84.5 | | |



(WT816)

(WT816A)

Application




Outdoor



Office



School



Home

Line ID: @neonics



ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th