NK Analog Force Gauge

Product Description

The NK series analog Force Gauge with compact size, high accuracy, they are easy to operate and handy to carry out. and can show the unit of newton and kilogram at the same time, The PEAK/TRACK knob of it can switch between the peak value load test and the continuous load test, They are excellent products which can take the places of the old style force gauges, and widely applied in electric, high&low voltage electric appliance, hardware, automobile parts, lighter and ignition system, light industry, mechanical, textile and so on industries for test of pull or push load test insertion force or pull and destructive experiment



Technical Data

NK-20	NK-30	NK-50	NK-100	NK-200	NK-300	NK-500	NLB-20	NLB-30	NLB-50	NLB-100	NLB-200	NLB-300	NLB-500	ALB-4	ALB-10	ALB-20	ALB-40	ALB-10
20N /2kg	30N /3kg	50N /5kg	100N /10kg	200N /20kg	300N /30kg	500N /50kg	20N /4.4lb	30N /6.6lb	50N /11lb	10N /22lb	200N /44lb	300N /66lb	500N /110lb	45lb /2kg	11lb /5kg	22lb /10kg	45lb /20kg	110lb /50kg
2N /0.2kg	3N /3kg	5N /0.5kg	10N /1kg	20N /2kg	30N /3kg	50N /5kg	2N /0.4lb	3N /0.6lb	5N /1lb	10N /2lb	20N /4lb	30N /6lb	50N /10lb	100000000000000000000000000000000000000	LUCK CONTRACTOR	2.2lb /1.1kg	4.5lb /2.2kg	11lb /5.5kg
0.1N/ 20g	0.2N /20g	0.25N /50g	0.5N /100g	1.0N /200g	2.0N /200g	2.5N /500g	0.1N /0.04lb	Mark Committee		0.5N /0.2lb	1.0N /0.4lb	2.0N /0.4lb	2.5N /1.0lb		DOMESTIC OF THE PARTY OF THE PA	The second second	0.2lb /0.2kg	0.5lb /0.5kg
								1	0mm									
								260x	66x36m	m								
	20N /2kg 2N /0.2kg 0.1N/ 20g	20N 30N /3kg 2N 3N /0.2kg /3kg 0.1N/ 20g /20g	20N 30N 50N /2kg /3kg /5kg 2N 3N 5N /0.2kg /3kg /0.5kg 0.1N/ 0.2N 0.25N 20g /20g /50g	20N 30N 50N 100N /2kg /3kg /5kg /10kg 2N 3N 5N 10N /0.2kg /3kg /0.5kg /1kg 0.1N/ 20g /20g /50g /100g	20N 30N 50N 100N 200N /2kg /3kg /5kg /10kg 20kg 2N 3N 5N 10N 20N /0.2kg /3kg /0.5kg /1kg /2kg 0.1N/ 20g /20g /50g /100g /200g	20N 30N 50N 100N 200N 300N /2kg /3kg /5kg /10kg /20kg /30kg 2N 3N 5N 10N 20N 30N /0.2kg /3kg /0.5kg /1kg /2kg /3kg /3kg 0.1N/ 0.2N 0.25N 0.5N 1.0N 2.0N /20g /200g	20N 30N 50N 100N 200N 300N 500N /2kg /3kg /5kg /10kg /20kg /30kg /50kg 2N 3N 5N 10N 20N 30N 50N /0.2kg /3kg /0.5kg /1kg /2kg /3kg /5kg 0.1N/ 0.2N 0.25N 0.5N 1.0N 2.0N 2.5N 20g /20g /50g /100g /200g /200g /500g	20N 30N 50N 100N 200N 300N 500N 20N /2kg /3kg /5kg /10kg /20kg /30kg /50kg /4.4lb 2N 3N 5N 10N 20N 30N 50N 2N /0.2kg /3kg /0.5kg /1kg /2kg /3kg /5kg /0.4lb 0.1N/ 0.2N 0.25N 0.5N 1.0N 2.0N 2.5N 0.1N /20g /200g /500g /0.04lb	20N 30N 50N 100N 200N 300N 500N 20N 30N /2kg /3kg /5kg /10kg /20kg /30kg /50kg /4.4lb /6.6lb 2N 3N 5N 10N 20N 30N 50N 2N 3N /0.2kg /3kg /0.5kg /0.5kg /1kg /2kg /3kg /5kg /0.4lb /0.6lb 0.1N/ 0.2N 0.25N 0.5N 1.0N 2.0N 2.5N 0.1N 0.2N /20g /200g /200g /500g /0.04lb /0.04lb	20N 30N 50N 100N 200N 300N 500N 20N 30N 50N /3kg /3kg /10kg /10kg /20kg /30kg /50kg /4.4lb /6.6ib /11lb 2N 3N 5N 10N 20N 30N 50N 2N 3N 5N /0.2kg /3kg /0.5kg /1kg /2kg /3kg /5kg /0.4lb /0.6lb /1lb 0.1N/ 0.2N 0.25N 0.5N 1.0N 2.0N 2.5N 0.1N 0.2N /0.04lb /0.04lb /0.01lb 10mm	20N 30N 50N 100N 200N 300N 500N 20N 30N 50N 10N /2kg /3kg /5kg /10kg /20kg /30kg /50kg /4.4lb /6.6lb /11lb /22lb /2N 3N 5N 10N 20N 30N 50N 2N 3N 5N 10N /0.2kg /3kg /0.5kg /1kg /2kg /3kg /5kg /0.4lb /0.6lb /1lb /2lb /0.1N/ 20g /20g /50g /100g /200g /200g /500g /0.04lb /0.04lb /0.04lb /0.1lb /0.2lb /0.2lb	20N 30N 50N 100N 200N 300N 500N 20N 30N 50N 110N 200N 720kg 730kg 750kg 74.4lb 76.6lb 711lb 722lb 744lb 70.2kg 73kg 70.5kg 70.5kg 70.4lb 70.6lb 71lb 72lb 74lb 70.1kg 720g 720g 7200g 7200	20N 30N 50N 100N 200N 300N 500N 20N 30N 50N 20N 110N 200N 300N 72kg 73kg 75kg 710kg 72kg 73kg 70.5kg 71kg 72kg 73kg 75kg 70.4kb 76.6kb 71kg 72kg 73kg 70.5kg 71kg 72kg 73kg 75kg 70.4kb 70.6kb 71kb 72kb 74kb 76.6kb 71kb 72kb 74kb 76kb 72kg 73kg 70.4kb 70.6kb 71kb 72kb 74kb 76kb 72kg 73kg 72kg 72kg 72kg 72kg 72kg 72kg 72kg 72	20N 30N 50N 100N 200N 300N 500N 20N 30N 50N 10N 22lb 30N 300N 500N 20N 30N 50N 11lb 30N 30N 50N 110N 20N 30N 50N 2N 3N 5N 10N 20N 30N 50N 2N 3N 5N 10N 20N 30N 50N 30N 30N 50N 30N 50N 30N 30N 30N 30N 30N 30N 30N 30N 30N 3	20N 30N 50N 100N 200N 300N 500N 20N 30N 50N 10N 220N 300N 500N 45lb 72kg 73kg 75kg 710kg 720kg 730kg 750kg 74.4lb 76.6lb 711lb 72lb 74lb 766lb 7110lb 72kg 2N 3N 5N 10N 20N 30N 50N 75kg 70.4lb 70.5kg 70.5kg 70.5kg 70.4lb 70.6lb 71lb 72lb 74lb 76lb 710lb 70.2kg 73kg 720g 720g 720g 720g 7200g 7200g 7500g 70.04lb 70.04lb 70.04lb 70.1lb 70.2lb 70.4lb 70.4lb 70.4lb 70.02kg 70.04lb 70.0	20N 30N 50N 100N 200N 300N 500N 20N 30N 50N 10N 200N 300N 500N 45lb 11lb /2kg /3kg /5kg /10kg /20kg /30kg /50kg /4.4lb /6.6lb /11lb /22lb /44lb /66lb /110lb /2kg /5kg /5kg 2N 3N 5N 10N 20N 30N 50N 2N 3N 5N 10N 20N 30N 50N 4.5lb 1lb /0.2kg /3kg /0.5kg /1kg /2kg /3kg /5kg /0.4lb /0.6lb /1lb /2lb /4lb /6lb /10lb /0.2kg /0.5kg /0.5kg /0.5kg /0.5kg /0.5kg /0.5kg /0.00g /0.04lb /0.04lb /0.1lb /0.2lb /0.4lb /0.4lb /0.4lb /0.4lb /0.04lb /0.05kg /0.05kg /0.05kg /0.05kg /0.05kg /0.05kg /0.05kg /0.00kg /0.05kg /0.00kg /0.00	20N 30N 50N 100N 200N 300N 500N 20N 30N 50N 20N 30N 66lb 711lb 722lb 744lb 766lb 7110lb 72kg 75kg 710kg 72kg 73kg 70.5kg 70.4lb 70.6lb 71lb 72lb 74lb 76lb 710lb 70.2kg 70.5kg 71.1kg 72kg 73kg 72kg 72kg 72kg 72kg 72kg 72kg 72kg 72	/2kg /3kg /5kg /10kg /20kg /30kg /50kg /4.4lb /6.6lb /11lb /22lb /44lb /66lb /110lb /2kg /5kg /10kg /20kg 2N 3N 5N 10N 20N 30N 50N 2N 3N 5N 10N /0.5kg /1kg /2kg /3kg /5kg /0.4lb /0.6lb /1lb /2lb /4lb /6lb /10lb /0.2kg /0.5kg /1.1kg /2.2kg 0.1N/ 0.2N 0.2N 0.5N 1.0N 2.0N 2.5N 0.1N 0.2N 0.2SN 0.5N 1.0N 2.0N 2.5N 0.02lb 0.05lb 0.1lb 0.2lb /0.2kg /0.5kg /1.0kg /0.2kg /0.5kg /0.1kg /0.2kg /0.2kg 10mm

AWG Digital torque wrench

Product Description

Digital torque wrench is different from general torque wrench, it has strong operation function including torque setting, time setting, mode setting, data storage, data clear, data output and user calibration function. It is easy to operate, it reduce the requirements for the operator by install the digital display. It is widely used for the automotive industry, machinery industry, such as bolt fastening and control.

Features

- Digital torsional readings
- Accuracy +/-2(range 20~100%)
- Clockwise and counterclockwise both operated
- Peak hold and real-time mode
- Buzzer and LED indication(reach preset torque value)
- Four units(ft-lb, in-lb, N-m, kgf.cm)
- 100 records can be stored
- Communication function
- Auto-shut down within 5 minutes

